

HSM type (Input voltage 230 V)								HTM type (Input voltage 400 V)			
Output voltage 0 ÷ 230 V			Output voltage 0 ÷ 260 V					Output voltage 0 ÷ 400 V			
Type	Is (A)	P (VA)	Type	Is (A)	P (VA)	Mass (kg)	Model	Type	Is (A)	P (VA)	
HSM 230/3	3.0	690	HSM 260/2.5	2.5	650	4.5	M50	HTM 400/3	3.0	2070	
HSM 230/4.5	4.5	1035	HSM 260/3.5	3.5	910	5.6	M100	HTM 400/4.5	4.5	3105	
HSM 230/6	6.0	1380	HSM 260/4.5	4.5	1170	5.6	M100	HTM 400/6	6.0	4140	
HSM 230/8	8.0	1840	HSM 260/6.3	6.3	1638	8.0	M200	HTM 400/8	8.0	5520	
HSM 230/10	10.0	2300	HSM 260/8	8.0	2080	8.0	M200	HTM 400/10	10.0	6900	
HSM 230/12	12.0	2760	HSM 260/10	10.0	2600	10.2	M250	HTM 400/12	12.0	8280	
HSM 230/18	18.0	4140	HSM 260/15	15.0	3600	14.3	M300	HTM 400/18	18.0	12420	
HSM 230/23	23.0	5290	HSM 260/20	20.0	5200	15.0	M400	HTM 400/23	23.0	15870	
HSM 230/32	32.0	7360	HSM 260/30	30.0	7800	21.5	M500	HTM 400/32	32.0	22080	

					Dimensions											
Output voltage 0 ÷ 450 V					Model	a	b	c	d	e	f	g	h	i	k	Drawing
Type	Is (A)	P (VA)	Mass (kg)	Model	M30	147	198	110	100	100	25	∅4.5	-	-	-	1
HTM 450/2.5	2.5	1950	12.9	3/M50	M50	147	198	110	100	100	25	∅4.5	-	-	-	1
HTM 450/3.5	3.5	2730	16.1	3/M100	M100	180	240	180	150	90	20	∅9	-	-	-	1
HTM 450/4.5	4.5	3510	16.1	3/M100	M200	180	240	180	150	90	20	∅9	-	-	-	1
HTM 450/6.3	6.3	4914	24.6	3/M200	M250	180	240	180	150	90	20	∅9	-	-	-	1
HTM 450/8	8.0	6240	24.6	3/M200	M300	238	375	170	178	-	-	∅10.5	-	-	-	2
HTM 450/10	10.0	7800	30.8	3/M250	M400	238	310	170	216	-	-	∅10.5	-	-	-	2
HTM 450/15	15.0	11700	46.5	3/M300	M500	248	340	180	249	-	-	∅10.5	-	-	-	2
HTM 450/20	20.0	15600	49.0	3/M400	Model	a	b	c	d (d*)	e	f	g	h	i	k	Drawing
HTM 450/30	30.0	23400	71.5	3/M500	3/M50	114	284	323	110	124	64	∅7	18	149	460	3
					3/M100	343	284	370	110	130	67	∅7	21	153	510	3
					3/M200	343	284	370	160	178	90	∅9	21	200	510	3
					3/M250	343	284	370	160	178	90	∅9	21	200	510	3
					3/M300	-	-	402	178*	275	138	-	-	275	605	3
					3/M400	-	-	402	216*	310	155	-	-	310	600	3
					3/M500	-	-	466	249*	350	175	-	-	350	660	3